


MIROR VAPORTIGHT HI-BAY

MWH
T5 & T8


- ◆ Fiber Glass Reinforced Polyester Body
 - ◆ Polycarbonate or Clear Acrylic Lens
 - ◆ Closed Cell Polyurethane Gasket
 - ◆ 4 lamp T5 & 6 Lamp T8 up to 104°F, & 6 lamp T5 up to 77°F
 - ◆ NSF/ANSI Standard 2- Splash Zone
 - ◆ NEMA 4X - Indoor or Outdoor use
 - ◆ IP67 - Dust and Liquid Protected
 - ◆ RoHS Compliant
 - ◆ High Pressure Hose Down 1500 PSI
 - ◆ High Ambient and -20°F Cold start ballast options available
 - ◆ UL Listed for US & Canada
 - ◆ T8 lamps maintain over 90% of their original output and provide good color rendition
 - ◆ T5HO lamps maintain 95% of their original output and provide much better color rendition
 - ◆ Consumes 50% of the energy of a 400 watt metal halide and delivers comparable light levels, when replaced one-for-one
 - ◆ Just under 4" tall - allows placement near the ceiling for the optimal usage of space Electronic ballast standard
 - ◆ All reflective surfaces constructed of enhanced specular anodized aluminum
 - ◆ Housing constructed of heavy gauge die-formed cold rolled steel
- Optical Efficiency = 93%
CRI = 85, High output lamps can be requested
High Frequency Electronic Ballast > 40 kHz
UL Listed & 5 Year Ballast Warranty
High Power Factor > 98% Ballast for 4FT lamps
the total harmonic distortion < 20% at full light output



Depth: 5.95"

DIMENSIONS

Width 14.61" x Length 51.81" x Depth 5.95"



ORDERING GUIDE

MWH	5	-	6L	-	OS	-	42B	-	UNV
SERIES	TYPE		TOTAL LAMPS		OPTIONS		BALLAST TYPE		VOLTAGE

SERIES

MWH MIROR Vaportight Hi-Bay Fixture

TYPE

5 54 watt T5HO
8 32 watt T8

TOTAL LAMPS (ship w/ fixtures - 841K)

4L 4 lamps
6L 6 lamps

OPTIONS (ship with fixture)

OS Occupancy Sensor*
6C Cord, 6' length, black
6C15TP 6' black cord, 15 amp, twistlock plug (voltage specific)
6C20TP 6' black cord, 20 amp, twistlock plug (voltage specific)
HUB 3/4" cast iron hub and junction box
HH Hub mount and hook
F32/841 Fluorescent lamp, 32 watt, 4100K (CEE Approved)
F32/850 Fluorescent lamp, 32 watt, 5000K
F54/841 Fluorescent lamp, 54 watt, 4100K
F54/850 Fluorescent lamp, 54 watt, 5000K
E8 Emergency ballast, T8
E5 Emergency ballast, T5
CA Clear Acrylic Lens
PC Polycarbonate Lens

BALLAST TYPE

2B (1) 2 lamp ballast
33B (2) 3 lamp ballasts
42B (1) 4 lamp & (1) 2 lamp ballast
222B (3) 2 lamp ballasts

(CEE Approved Ballast Available)

VOLTAGE

120 120V
208 208V
240 240V
277 277V
UNV 120 - 277V
347** 347V
480**/** 480V

ACCESSORIES (ship separately)

Y Y-hanger (1 pair)
Y3 Y-hanger & 3' chain (1 pair)
G10 Gripple Hang-Fast Suspension, 10' length (1 pair)



* Fixtures equipped with occupancy sensor must have a specified input voltage
** Only available in 2 lamp ballasts
*** Ballast(s) are 277V input. T8 Fixture furnished with 480/277V step down transformer. Fixture accepts 480V supply voltage.