


MIROR

RETROFIT KIT (2x2 & 2x4) TROFFER T5 & T8

MRFT

- ◆ Enhance light levels and quality
- ◆ Multiple reflector options
 - 95% Enhanced Aluminum
 - 91% White Aluminum
 - White formed steel ballasts cover
- ◆ Multiple lamp and ballast options
 - T5 HO or T8
 - Super T8 High efficiency
- ◆ Easy installation
- ◆ CRI = 85, High output lamps can be requested
- High Frequency Electronic Ballast > 40 kHz
- UL Listed & 5 Year Ballast Warranty
- High Power Factor > 98%
- Ballast for 4FT lamps the total harmonic distortion < 20% at full light output
- ◆ Standard Kit Includes:
 - Reflector
 - Brackets
 - Quarter Turns
 - Tek Screws
 - Ballast



No replacement necessary for up to 25 years
 Standard sized for all 2X2 & 2X4 Strips
 25 reflector designs for maximum efficiency
 UL Classified as a ballast cover
 Allows tandem wiring in some applications

Rounded edge brackets for installation safety
 Standard brackets designed to fit most fixtures
 Tek screw slots for easy bracket centering
 Clip in reflector for easy installation

ORDERING GUIDE

MRFT	-	T8	-	2X4	-	2L	-	EA	-	2B	-	UNV
SERIES		TYPE		SIZE		TOTAL LAMPS		OPTIONS		BALLAST TYPE		VOLTAGE

SERIES

MRFT	T8 KIT
MRFT	T5 KIT

OPTIONS (ship with fixture)

EA	95% Enhanced Aluminum
W	91% White Aluminum

BALLAST TYPE

2B	(1) 2 lamp ballast
4B	(1) 4 lamp ballast
33B	(2) 3 lamp ballast

(CEE Approved Ballast Available)

TYPE

T8	17 watt T8 / 32 watt T8
T5	24 watt T5 / 54 watt T5

ACCESSORIES (ship separately)

LAMPS ARE SOLD IN CASE QTY AND ARE SHIPPED SEPARATELY.

F32/841	Fluorescent lamp, 32 watt, 4100K (CEE Approved)
F32/850	Fluorescent lamp, 32 watt, 5000K
F54/841	Fluorescent lamp, 54 watt, 4100K
F54/850	Fluorescent lamp, 54 watt, 5000K

VOLTAGE

120	120V
208	208V
240	240V
277	277V
UNV	120-277V
347**	347V
480***	480V

SIZE

2x2	2X2 Troffer Kit
2x4	2X4 Troffer Kit

TOTAL LAMPS

2L	2 lamps
3L	3 lamps
4L	4 lamps
6L	6 lamps

** Only available in 2 lamp ballasts
 *** Ballast(s) are 277V input. Fixture furnished with 480/277V step down transformer. Fixture accepts 480V supply voltage

